# Quality data for petrol and diesel fuel in Iceland 2017

-June 2018



# **Table of Contents**

1.	INTRODUCTION	1
1.1.	Background Information	1
1.2.	Details of those compiling the fuel quality monitoring report	1
2.	GENERAL INFORMATION	2
2.1.	Short description of fuel grades and distribution of fuels in Iceland	2
2.2.	Description of fuel quality monitoring system	2
2.3.	Total sales of petrol and diesel	2
2.4.	Defination of summer period for petrol volatility	2
3.	QUALITY DATA FOR PETROL AND DIESEL FUEL	3
3.1.	Quality data for petrol	3
3.2.	Quality data for diesel fuel	4





### 1. Introduction

#### 1.1. Background Information

With reference to Directive 98/70/EC of the European Parliament and of the Council of 13 October 1998 relating to the quality of petrol and diesel, Article 8(3) and Commission Decision C (2002) 508 of 18 February 2002 we hereby send the report on the quality data of petrol and autodiesel fuels used on the Icelandic market in the year 2017. Directive 98/70/EC is transposed into Icelandic legislation with regulation 560/2007.

This report contains the above information for quality offuel marketed in Iceland in the year 2017.

#### 1.2. Details of those compiling the fuel quality monitoring report

Table 1.1. Details

Reporting year	2017					
Country	Iceland					
Date report completed	20 June 2018					
Institute responsible for report	The Environment Agency of Iceland					
Address of institute	Sudurlandsbraut 24, Reykjavik, Iceland					
Person responsible for report	Eirikur Thorir Baldursson					
Telephone no.	+354 591 2000					
E-mail	<u>ust@ust.is</u>					



### 2. General information

## 2.1. Short description of fuel grades and distribution of fuels in Iceland

In Iceland, the main fuel grades are 95 octane (Mogas 95/EN228) and auto diesel. Over 95% of all gasoline sold is Mogas 95/EN228.

There are four main oil companies in Iceland; Atlantsolía ehf, Skeljungur hf., Olíuverzlun Íslands hf. and N1 hf. In 2017 the total amount of fuel delivered to road transport was 354,2 kilotonnes and the distribution of fuel was covered from multiple depots that are spread around the country.

#### 2.2. Description of fuel quality monitoring system

In Iceland, each fuel batch delivery is controlled by Fjölver laboratory and fuel inspection. The testing results of the fuel products are directly compared with the agreed product requirements and are accepted if the results are within given specifications. The data of delivered fuel batches are reported to the competent authority; The Environment Agency of Iceland.

#### 2.3. Total sales of petrol and diesel

The total sales of petrol and diesel in 2017 in Iceland are summarized in table 2.1.

**Table 2.1.** Total sales of petrol and diesel

Fuel grade	Total national sales (ltr. at 15°C)
Unleaded petrol (95≤RON≤98), Mogas 95/98/EN228	184.776.126
Diesel fuel <sup>1</sup> (Road transport only)	261.011.584

<sup>1:</sup> As specified in Annex II of directive 98/70/EC

#### 2.4. Definition of summer period for petrol volatility

Due to low ambient summer temperatures in Iceland, the summer period is from 1 June to 31 August and the maximum vapour pressure is 70 kPa.



# 3. Quality data

#### 3.1. Quality data for petrol

The summary report for the quality monitoring data for petrol collected in the year 2017 is shown in table 3.1.

Table 3.1. Quality monitoring data

Parameter	Unit	Unit Analytical and statistical results			results	Limiting value <sup>1</sup>				
							National specification		According to 98/70/EB	
		No. of samples	Minimum	Maximum	Mean	Minimum	Maximum	Minimum	Maximum	
Density	kg/L	61	0,7212	0,7471	0,7324					
Research octane No	_	61	93,5	95,5	94,6	95		93,5	_	
Motor octane No	_	61	84,5	85,7	85,0	85		84,5		
Vapour pressure, DVPE	kPa	61	59,8	100	83,6	*	*	*	*	
Distillation:										
— evaporated at 100 °C	%(v/v)	61	48,6	65,1	58,4	46	_	46	_	
— evaporated at 150 °C	%(v/v)	61	83,1	93,3	81,5	75	_	75	_	
Hydrocarbon analysis:										
— olefin	%(v/v)	61	4,3	16,4	10,4	_	18		18,8	
— aromatics	%(v/v)	61	21,7	34,7	27,8	_	35		36,5	
— benzene	%(v/v)	61	0,88	1,04	0,97	_	1		1,04	
Oxygen content	%(m/m)	61	0,1	1,9	0,6		2,7	_	2,7	
Oxygenates:										
— Methanol	%(v/v)	61	0	0,5	0,2		3	_	3	
— Ethanol	%(v/v)	49	0	4,9	1,7		10	_	5	
— Iso-propyl alcohol	%(v/v)	61	0	0,5	0,2	_	12	_	10	
— Tert-butyl alcohol	%(v/v)	61	0	0,5	0,2	_	15	-	7	
— Iso-butyl alcohol	%(v/v)	61	0	0,5	0,2	_	15	_	10	
— Ethers with five or more carbon atoms per molecule	%(v/v)	61	0	0,1	0,1	_	22	_	15	
<ul><li>other oxygenates</li></ul>	%(v/v)	42	0	1,7	0,3	_	15	_	10	
Sulphur content	mg/kg	61	3,7	10,0	8,2	_	10	_	10	
Lead content	g/l	61	<0,003	<0,003	<0,003	_	0,005	_	0,005	

<sup>(1)</sup> The limiting values are "true values" and were established according to the procedures for limit setting in EN ISO 4259:1995

<sup>\*</sup>Iceland is an outermost region with a maximum vapous pressure of 70kPa during the summer time.



Table 3.2. Number of petrol samples taken each month

Month	Number of samples taken
January	4
February	3
March	2
April	3
May	4
June	7
July	6
August	12
September	6
October	5
November	5
December	4
Total	61

#### 3.2. Quality data for diesel fuel

The summary report for the quality monitoring data for diesel fuel in the year 2017 is shown in table 3.3.

Table 3.3. Quality monitoring data

Parameter	Unit	Analytical and statistical results				Limiting value <sup>1</sup>			
							ional ication		ding to 70/EB
		No. of samples	Minimum	Maximum	Mean	Minimum	Maximum	Minimum	Maximum
Cetane No.	_	34	51	53	51,9	51		51	_
Density at 15°C	kg/L	34	840,0	844,6	840		845	_	845
Distillation — 95% point	°C	0	-	-	-		360	_	360
Polycyclic aromatic hydrocarbons	%(m/m)	30	2	6	4,1		11	_	11
Sulphur content	mg/kg	30	3	10	8,2		10	_	10
Specific energy NCV. Calc.	MJ/Kg	30	43,1	43,2	43,1				

<sup>(1)</sup> The limiting values are "true values" and were established according to the procedures for limit setting in EN ISO 4259:1995



Table 3.4. Number of diesel fuel samples taken each month

Month	Number of samples taken
January	2
February	3
March	1
April	3
May	3
June	3
July	4
August	4
September	3
October	3
November	3
December	2
Total	34